



Trans D3 Automatic Transmission Fluid

TECHNICAL DATA SHEET

Product Description:

Veedol Trans D3 is a premium quality automatic transmission fluid formulated from highly superior base oils and latest technology additive system to meet the demanding requirements of Dexron III and other major OEM performance specifications. Veedol Trans D3 is engineered for use in hydraulic systems of most automatic transmission systems where a fluid type GM DEXRON III is required.

Performance Specifications:

Meets & exceeds the performance requirements of

- General Motors DEXRON IIIH/ IIIG/ IIE/ IID
- General Motors Type A Suffix A (TASA)
- Ford vehicles (pre-2005)
- Allison TES 389
- Allison C-4

Features/Benefits:

- Excellent oxidation stability and clutch friction durability
- Improved low temperature performance for more efficient cold – starting.
- Minimizes sludge & varnish formation and keeps system clean.
- Protects parts against rusting even during idle conditions.
- Excellent elastomer compatibility

Application:

Recommended for use in automatic and powershift transmissions of passenger cars, light commercial and industrial vehicles requiring Dexron III fluid.

Typical Properties:

Test Parameter	ASTM Test Method	Typical Values
Kinematic Viscosity, @ 100°C, cSt	ASTM D 445	7.5
Viscosity Index	ASTM D 2270	180
Flash Point (COC), °C	ASTM D 92	218
Pour Point, °C	ASTM D 97	-45

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.